

C182P KIT**SLUMP CONE, PLASTIC**, complete set including:

- C181P** Slump Cone, **plastic**. Max. temperature: 40 °C
Weight: 750 g
- C180-02** Tamping rod, galvanized steel, Ø 16x600 mm
- C180-04** Base plate, galvanized steel
- V176-01** Stainless steel rule, 300 mm long
- V184** Aluminium scoop, 500 cc capacity
- V178-01** Fine wire brush

Weight: 5 kg approx.**ACCESSORY**

- C180-03P** Cone Filling Funnel, **plastic**. Weight: 250 g

 **Note:** Each component of this kit can be ordered separately.

C180-01

SLUMP CONE only, manufactured from **stainless steel**, diameter 100/200 mm, height 300 mm, thickness 1.5 mm

Weight: 2 kg approx.**C181**

SLUMP CONE only, **galvanized steel**, Ø 100/200 mm, height 300 mm, thickness 1.5 mm

Weight: 2 kg approx.**V185-03****SCOOP, STAINLESS STEEL**

STANDARD: EN 12350-1

Used to sample fresh concrete
Capacity: 5 kg of concrete
Dimensions: Ø 125x250 mm

C185**COMPACTING FACTOR APPARATUS**

STANDARD: BS 1881:103

Designed to undertake a more precise and sensitive test procedure than the simple slump test.

The apparatus consists of two conical hoppers mounted on a cylinder. Each hopper has a hinged flange with quick release mechanism and everything is mounted on a rigid steel stand.

The compacting factor is the ratio between the weight of the partially compacted concrete and the weight of the fully compacted concrete. Supplied complete with tamping rod diameter mm 16x600 long.

Dimensions: 500x400x1510 mm**Weight:** 55 kg approx.**C192 KIT**
FLOW TABLE

STANDARDS: EN 12350-5 | DIN 1048

The apparatus comprises a galvanized steel conical mould, Ø 130/200x200 mm, double steel flow table with galvanized top plane, guide device, wooden tamper. Used to determine the workability of concrete. The top table has a square surface of 700x700 mm, hinged on one side.

Weight: 30 kg approx.**SPARES**

- C192-01** Conical mould, galvanized steel made, Ø 130/200x200 mm

- C192-02** Wooden tamper